

# CITIZEN

Micro HumanTech

## Product Versions

### Internal Peel & Rewind

The CL-S700R features an integrated peeler with liner re-winder for easy label dispensing. The peel sensor waits for each label to be taken before printing another.



### 300 dpi Resolution

The CL-S703 is ideal for small labels with 2D matrix barcodes such as Datamatrix, DataBar, QR-Code and PDF417 or printing company logos and idents and CE or WEEE logos.



## Printer Specifications

Model Version	CL-S700DT	CL-S700	CL-S700R	CL-S703	CL-S703R*
Technology	Direct Thermal	Thermal Transfer & Direct Thermal			
Resolution	203 dpi (8 dots per mm)			300 dpi (12 dots per mm)	
Print Speed (maximum)	7 ips, 175mm/sec	10 inches per second (254 mm / second)		8 inches per second (200 mm / second)	
Print Width (maximum)	4.10 inches, 104.1 mm				
Media Width (min to max)	1.00 inches to 4.65 inches (25.4 mm to 118.1 mm)				
Media Length (min to max)	0.25 inches to 32.0 inches (6.35 mm to 812.8 mm)				
Roll Size (max), Core Size (min)	8 inches (200 mm) outside diameter. Core size minimum of 1 inch (25mm). External media slot				
Media Sensor	Fixed front sensor	Fully adjustable rear sensor and high resolution front sensor			
Media Thickness (min to max)	0.0025 inches - 0.01 inches (0.0635 - 0.254 mm)				
Ribbon Size		3.40 inches (86.5 mm) maximum Outside Diameter. 1476 ft (450 metres) length.			
Ribbon Winding & Type	Direct thermal only	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type			
Ribbon System		ARCP™ automatic ribbon tension adjustment			
Emulations (Languages)	Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400®				
Standard Interfaces	Serial & USB	Parallel (IEEE-1284), Serial (RS-232C), USB (version 1.1)			
Optional Interfaces	Parallel, LAN, WLAN	Ethernet LAN (10/100 BaseT), Wireless LAN (802.11b, g, n*)			
Case Type, Mechanism Type	Hi-Open™ metal case with safe, soft-close feature. Hi-Lift™ mechanism with 90° opening				
Control Panel	4-line back-lit graphic LCD and 4 buttons				
RAM (Standard Memory)	16.0 Mb total, 1.0 Mb available for user				
Flash (Non-Volatile Memory)	4.0 Mb total, 1.0 Mb available for user				
Windows® drivers, design software	Free-of-charge on CD with printer, including support for Windows® XP®, 2003, 2008, Vista®				
Internal Peeler & Rewinder	No	No	Yes	No	Yes
Size (W x D x H mm)	255 x 490 x 265	255 x 490 x 265	255 x 490 x 385	255 x 490 x 265	255 x 490 x 385
Weight (approximately)	12.5 Kg	13.3 Kg	17.6 Kg	13.3 Kg	17.6 Kg
Warranty	2 Year Manufacturer's Warranty or 100 Km on printer. Printhead: 50 Kms or 6 months in TT mode				

# CITIZEN CL-S700

LABEL & BARCODE

## Features

- Hi-Lift™ mechanism for easy ribbon and media loading.
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- Cross-Emulation™: Zebra® and Datamax® languages standard and automatically selected.
- Backlit LCD control panel for easy configuration.
- Front access for all operations including media and ribbon changing.
- Power switch located in recess at front of printer.
- Adjustable media sensor as standard with label gap and black mark sensing.
- Ingenious front-loading re-winder for peeling or batch mode.
- Optional Wireless LAN and Ethernet, cutters and peelers

Dealer Stamp

1200000